


Features & Options

- Probe Lengths: 2", 4" and 8" (fit standard BAPI Thermowell lengths)
- Series 304 Stainless Steel Probes
- Double Encapsulated Sensors
- Three Optional Enclosures

Immersion Units are available in 2", 4" and 8" probe lengths. This unit is provided with a 1/4" stainless steel probe and a 1/2" NPT double-ended stainless steel fitting.

The sensors are potted inside the probe with a thermally conductive compound. All units have etched Teflon leadwires and double encapsulated sensors to create a watertight package that can withstand high humidity and condensation. Immersion Probes are available with a metal Weatherproof enclosure, or a polycarbonate BAPI-Box Crossover or BAPI-Box 2.



Weatherproof Standard Mount (below) and Outside Mount (left)

No Box

BAPI-Box 2 Standard Mount (below) and Outside Mount (right)

BAPI-Box Crossover Standard Mount (below) and Outside Mount (right)

Specifications

Environmental Operation Range:
 Temperature Sensor: -40 to 105 °C
 Humidity: 0 to 100%, non-condensing

Enclosure Material:
 Weatherproof: Cast Aluminum
 BAPI-Box 2: UV-res. Polycarb., UL94 V-0
 BAPI-Box Crossover:
 Cover: Polycarbonate, UL94 V-0
 Base: Nylon, UL94 HB

Sensing Element: Thermistor or RTD
 (See Sensors Section for Specs.)

Probe Material: Stainless Steel, 1/4" dia.

Enclosure Rating:
 Weatherproof: IP24, NEMA 3R

BAPI-Box Crossover:
 IP10, NEMA 1
 (IP44 with knockout plug in open port)

BAPI-Box 2: IP66, NEMA 4X

Encl. Dimensions: H x W x D
 BAPI-Box Crossover:.....3.1 x 2.2 x 1.9" (79 x 56 x 49mm)
 Weatherproof.....4.5 x 2.75 x 2.2" (114 x 70 x 55mm)
 BAPI-Box 2:.....4.9 x 2.8 x 2.35" (125 x 71.6 x 60mm)

(For enclosure dimension drawings, turn to the end of the section.)



Submittal sheets without List Prices are available on our website at www.bapivac.com

Use the Option Selection Guide below to create your custom part number. Replace the number and parenthesis with the designator for each selection. Skip the designator and dashes for optional selections that are not required in your configuration.

Immersion Sensor with SS Fitting Option Selection Guide

BA/ (#1) - (#2) - (#3) - (#4)

#1: Temperature Sensor (required)	List Price
1.8K 1.8K Thermistor	\$18
3K 3K Thermistor	\$18
10K-2 10K-2 Thermistor	\$18
10K-3 10K-3 Thermistor	\$18
10K-3[11K] 10K-3[11K] Thermistor	\$18
20K 20K Thermistor	\$18
1K[375] 1K Platinum RTD (375 curve)	\$25
1K[NI] 1K Ω Nickel RTD	\$65
1K 1K Platinum RTD (385 curve)	\$25

Transmitters below require a BAPI-Box 2 Enclosure

T1K[32 TO 212F] 1K Plat. RTD Transmitter, 4 to 20 mA Output, 32 to 212°F Range	\$125
T1K[20 TO 120F] 1K Plat. RTD Transmitter, 4 to 20 mA Output, 20 to 120°F Range	\$125
T1K[0 TO 100F] 1K Plat. RTD Transmitter, 4 to 20 mA Output, 0 to 100°F Range	\$125
T1K[0 TO 100C] 1K Plat. RTD Transmitter, 4 to 20 mA Output, 0 to 100°C Range	\$125
T1K[-7 TO 49C] 1K Plat. RTD Transmitter, 4 to 20 mA Output, -7 to 49°C Range	\$125
T1K[-18 TO 38C] 1K Plat. RTD Transmitter, 4 to 20 mA Output, -18 to 38°C Range	\$125

Matched Transmitters are also available. Contact your BAPI representative for ordering.

#2: Probe Type and Length (required)	List Price
I-2"-SS Immersion, SS Fitting, 2" (51mm) length - Use 2" BAPI Thermowell	\$42
I-4"-SS Immersion, SS Fitting, 4" (102mm) length - Use 4" BAPI Thermowell	\$42
I-8"-SS Immersion, SS Fitting, 8" (203mm) length - Use 8" BAPI Thermowell	\$42

#3: Enclosure Style and Probe Mount (required)	List Price
BBX BAPI-Box Crossover (IP10, NEMA 1)	\$0
BBXO BAPI-Box Crossover (IP10, NEMA 1), Outside Mount (probe out bottom)	\$0
BB2 BAPI-Box 2 (IP66, NEMA 4X)	\$12
BB2O BAPI-Box 2 (IP66, NEMA 4X), Outside Mount, (probe out the bottom)	\$12
WP Weatherproof (IP24, NEMA 3R)	\$12
WPO Weatherproof (IP24, NEMA 3R), Outside Mount, (probe out the bottom)	\$12

#4: Test & Balance or Terminal Strip (optional, requires a BAPI-Box Crossover Enclosure)	List Price
TB Test & Balance Switch	\$7.50
TS Terminal Strip Connection (The \$7 does not apply to T1K transmitter units)	\$7

Additional options are available for these units but not shown in this Selection Guide. Contact your BAPI representative for the complete list of options. Submittal sheets without List Prices can be downloaded from our website at www.bapivac.com

Example Number: BA/ (10K-2) - (I-2"-SS) - (BBX) - ()

Actual Number (with parenthesis removed): BA/10K-2-I-2"-SS-BBX

Description: 10K-2 Thermistor, Immersion Sensor with SS Fitting, BAPI-Box Crossover.

List Price: \$18 (10K-2 Thermistor) + \$42 (Probe 2" Length) = \$60 List Price

Your Number: BA/

