



## Features & Options

### BA/LI14505

The BA/LI14505 Lithium AA battery is the ideal replacement for all BAPI Bluetooth Low Energy wireless sensors (except the Wireless Food Probe). Each unit takes two batteries, except the BAPI-Stat “Quantum Slim” which takes only one battery.



**BA/LI14505**  
(for all BAPI Wireless Sensors except the Wireless Food Probe)

### BA/BAT-5AA-HIT

The BA/BAT-5AA-HIT High Temperature Lithium 1/2AA battery is the ideal replacement for the BAPI Bluetooth Low Energy Wireless Food Probe sensor. Each food probe takes one battery.



**BA/BAT-5AA-HIT**  
(for Wireless Food Probe)

<u>PART NUMBER</u>	<u>DESCRIPTION</u>
--------------------	--------------------

<b>BA/LI14505</b> .....	Lithium AA Battery, 3.6V, for all BAPI Bluetooth Low Energy Wireless sensors except the Wireless Food Probe
-------------------------	---

<b>BA/BAT-5AA-HIT</b> .....	Lithium 1/2AA Battery, 3.6V, for the BAPI Bluetooth Low Energy Wireless Food Probe
-----------------------------	--

## Specifications

### BA/LI14505 Battery

**Type & Size:** Lithium, AA

**Nominal Voltage:** 3.6V

**Nominal Capacity:** 2.6 Ah @ 1mA, to 2V

**Operation Temp:**

-67 to 185°F (-55 to 85°C)

0 to 95 %RH Non-Condensing

**Agency:** RoHS

### BA/BAT-5AA-HIT Battery

**Type & Size:** Lithium (High Temp), 1/2AA

**Nominal Voltage:** 3.6V

**Nominal Capacity:** 0.9 Ah @ 1mA, to 2V

**Operating Temp:**

-67 to 257°F (-55 to 125°C)

0 to 95 %RH Non-Condensing

**Agency:** RoHS

# Pluggable Terminal Blocks Kit




## Features & Options

Analog Output Modules (AOMs) plug into each other and the receiver as shown above. However, the AOMs may also be mounted remotely using the optional Pluggable Terminal Block Connectors which are available as a 4-connector kit.

**PART NUMBER:**

**BA/AOM-CONN** ..Pluggable Terminal Block Kit



**Optional Pluggable Terminal Block Kit for AOMs (4 Connectors)**